




SafeSign™ Breakaway System




Telespar® is proud to introduce the SafeSign™ breakaway system, designed to allow sign posts to breakaway after impact, protecting passengers from potentially dangerous situations. Designed for use with 4" square x 8 gauge posts and finished with Gatorshield® to prevent corrosion. A two post system has the ability to support a 120 ft² sign in a 90 mph wind zone.

The SafeSign™ breakaway system is designed to withstand the normal wear-and-tear from wind and weather. The hinge and slip base system will breakaway once impacted by a vehicle.

Tested and passed to MASH regulatory standards, the SafeSign™ allows sign installations to be FHWA complaint.

Assembled SafeSign™



Features and Benefits

- **Compliant with new MASH standard**
- Can hold signs commonly mounted on W6x9, W6x12, W6x15, and in some cases W8x18 beam posts
- Can be impacted from any direction, breaking away to protect vehicles and passengers from harm
- 4" post can be cut to length in the field, allowing for easy installation, reducing labor costs and work roadside exposure to traffic
- Designed so that after impact only the hardware and cylinder component of the hinge need to be replaced
- No torque wrench required for installation

Part Number	Description
191582	Hinge Assembly Kit (Hardware Included)
191583	13" Slip Base Kit (Hardware Included)
191585	13" Slip Base Winged Anchor
191586	13" Slip Base Anchor
Replacement Parts	
191598	Hinge Cylinder
191558	Hinge Center Bolt
191600	Slip Base Replacement Hardware Kit